



NO CABLES REQUIRED:

The inVENTer ventilation devices are controlled on an 868 MHz wireless frequency.

WORKS AT THE PUSH OF A BUTTON:

Intuitively set the ventilation level and mode directly on the control panel.

TAKES CARE OF EVERYTHING:

Connect to up to 4 or 8 Connect Inner Covers plus 2 sensors.

ADAPTS TO YOUR NEEDS:

Control indoor humidity and the carbon dioxide level as needed by integrating additional sensors.

BASIC CONNECT E4/E8

INTUITIVE WIRELESS CONTROL FOR INVENTER SYSTEMS

Basic Connect makes wireless ventilation even easier thanks to operation directly on the panel. The connected ventilation devices with Connect Inner Covers receive all necessary ventilation level and mode information at the push of a button. If a humidity sensor or an air quality sensor is also integrated, the ventilation adjusts as required to ensure a healthy indoor climate.

TECHNICAL SPECIFICATIONS

Control unit dimensions W x H x D [mm]	90 x 90 x 15
Radio frequency [MHz]	868
Radio network range [m]	Open field: 100 Building: 20
Mains voltage [V AC, Hz]:	230, 50
Operating voltage [V DC]	5
Power consumption max. [W]	0.6
Ingress protection / Protection class	IPX2 / II



All information and downloads at
www.inventer.eu

inVENTer GmbH
Ortsstraße 4a
D-07751 Löberschütz

Tel: +49 (0) 36427 211-0
info@inventer.de
www.inventer.eu